# Product datasheet

Specifications



## Kaedra - versatile - 340 x 460 mm - 17 pre-cutouts

13195

Discontinued on: 01-Nov-2020

Discontinued

## Main

| | |
|---|---|
| **Range** | Mureva |
| **product name** | Mureva Enclosure |
| **Product or component type** | Weatherproof enclosure |
| **enclosure type** | Versatile enclosure |
| **Mounting plate description** | Slotted |

## Complementary

| | |
|---|---|
| **Enclosure mounting** | Surface |
| **Electrical insulation class** | Double insulation<br>Class II |
| **Type of front cover** | Opaque |
| **Number of pre-cutouts PG ISO** | 17 |
| **Locking options description** | Optional keylock |
| **Enclosure material** | Self-extinguishing polymer |
| **Width** | 340 mm |
| **Height** | 460 mm |
| **Depth** | 160 mm |
| **Internal depth** | 130 mm |
| **Colour** | Enclosure: light grey (RAL 7035) |

## Environment

| | |
|---|---|
| **Standards** | IEC 60670<br>EN 50262<br>IEC 61439-3<br>IEC 60695-2-1 |
| **Fire resistance** | 650 °C conforming to IEC 60695-2-1 |
| **IP degree of protection** | IP65 conforming to IEC 60529 |
| **IK degree of protection** | IK09 conforming to EN 50102 |
| **Environmental characteristics (UV)** | UV resistant: class 3 conforming to ISO 4582:2010<br>Ultraviolet degradation test conforming to ISO 4892-2:2013 |
| **Overvoltage category** | II |
| **Ambient air temperature for operation** | -25…60 °C |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

## Packing Units

| | |
|---|---|
| **Unit Type of Package 1** | PCE |
| **Number of Units in Package 1** | 1 |
| **Package 1 Height** | 16.800 cm |
| **Package 1 Width** | 36.200 cm |
| **Package 1 Length** | 47.000 cm |
| **Package 1 Weight** | 3.165 kg |
| **Unit Type of Package 2** | P12 |
| **Number of Units in Package 2** | 28 |
| **Package 2 Height** | 80.000 cm |
| **Package 2 Width** | 80.000 cm |
| **Package 2 Length** | 120.000 cm |
| **Package 2 Weight** | 100.620 kg |

## Contractual warranty

| | |
|---|---|
| **Warranty** | 18 months |

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

### Environmental footprint

| | |
|---|---|
| Carbon footprint (kg.eq.CO2 per CR, Total Life cycle) | 18 |
| Environmental Disclosure | Product Environmental Profile |

## Use Better

### Materials and Substances

| | |
|---|---|
| Minimum percentage of recycled plastic content | 44 |
| Packaging made with recycled cardboard | Yes |
| Packaging without single use plastic | No |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) |
| SCIP Number | 5036b720-908f-495f-9f9e-e215274e05b0 |
| REACh Regulation | REACh Declaration |
| Halogen content performance | Halogen free product |

## Use Again

### Repack and remanufacture

| | |
|---|---|
| Circularity Profile | No need of specific recycling operations |
| Take-back | No |